

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 479 451 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
20.03.1996 Bulletin 1996/12

(51) Int. Cl.⁶: **B05B 11/00**

(21) Application number: **91308554.4**

(22) Date of filing: **19.09.1991**

(54) Hand operated sprayer with multiple fluid containers

Handbetriebener Zerstäuber mit mehreren Flüssigkeitsbehältern

Pulvérisateur manuel comprenant plusieurs réservoirs de fluides

(84) Designated Contracting States:
CH DE DK ES FR GB IT LI NL SE

(30) Priority: **01.10.1990 US 591526**

(43) Date of publication of application:
08.04.1992 Bulletin 1992/15

(60) Divisional application: **94120357.2**

(73) Proprietor: **TAKE 5**
Carson City, Nevada 89701-3206 (US)

(72) Inventor: **Proctor, Rudy Roy**
Hurricane, Utah 84737 (US)

(74) Representative: **Senior, Alan Murray et al**
J.A. KEMP & CO.,
14 South Square,
Gray's Inn
London WC1R 5LX (GB)

(56) References cited:

EP-A- 0 026 902	CA-A- 1 104 531
DE-A- 3 614 515	FR-A- 1 408 299
FR-A- 2 647 093	US-A- 4 013 228
US-A- 4 165 812	

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

EP 0 479 451 B1

Descripti n

The field of the present invention relates to devices for ejecting or spraying a fluid stream or spray through a nozzle from out of a container or bottle.

Heretofore, there have been various hand-held sprayers such as that disclosed in US-A-3 749 290 in which fluid from a container is pumped out by a pump mechanism comprised of a collapsible tubular bulb, the actuation of the trigger compressing the bulb to expel the fluid. Another type of trigger sprayer device is disclosed in US-A-4 013 228 in which the trigger actuates the piston and cylinder combination which alternately draws fluid in from the container and then expels it out through a nozzle.

These trigger-type sprayers draw fluid from a single container, the sprayer ejecting only that particular fluid and fluid concentration which is within the container.

CA-A-1 104 531 discloses a trigger sprayer in accordance with the precharacterising portion of claim 1 in which fluids can be drawn by action of the trigger from two chambers for mixing before ejection by the sprayer head. US-A-4 165 812 discloses an arrangement of containers which can be compactly connected together.

According to the present invention, there is provided a fluid dispensing apparatus for mixing and dispensing a first fluid from a first chamber and a second fluid from a second chamber, comprising a fluid dispensing head, including (a) a fluid outlet, (b) a pump chamber, (c) pumping means for (i) drawing fluid from the first and second chambers into the pump chamber at a desired fluid ratio via first and second fluid passages in communication with the first and second chambers and (ii) discharging fluid out of the pump chamber to the fluid outlet, and (d) actuator for actuating the pumping means, wherein actuation of the pumping means forces fluid from the pump chamber out through the fluid outlet, characterised in that the first fluid passage provides fluid communication for the first fluid from the first chamber to the pump chamber independently from the second fluid passage which provides fluid communication for the second fluid from the second chamber to the pump chamber, whereby the first and second fluid passages separately provide fluid communication from the first and second chambers into the pump chamber.

The apparatus may also include a bottle for use with the handheld fluid dispensing system for multiple containers, said bottle constructed and arranged in a substantially mating relationship to at least a second bottle of similar configuration and said bottle having a collar connector for permitting detachable connection to a handheld fluid dispensing device independent and separate from the second bottle.

Thus, a trigger sprayer, can selectively draw fluid out from at least two containers, mix the fluids in a desired concentration or ratio and expel the mixture of fluids out of a nozzle.

In a preferred embodiment, the containers or bottles connected to the sprayer device are selectively detach-

able for refilling a container with fluid or exchanging one of the containers with another container having an alternate fluid.

In another embodiment, the fluid selection control device is included for permitting operative selection of one, two or more containers.

The invention will be further described, by way of example, with reference to the accompanying drawings, in which:-

Figure 1 is a side elevation view of a two-bottle trigger sprayer according to the preferred embodiment of the present invention;

Figure 2 is the spray and bottle combination of Figure 1 in a partial cut-away view illustrating the internal mechanisms;

Figure 3 is a cross-sectional view of the spray bottle of Figure 1 taken along the line 3-3;

Figure 3a is a cross-sectional view of the bottle combination of Figure 2 taken along the line 3a-3a;

Figure 3b is a cross-sectional view of the spray bottle combination of Figure 2 taken along the line 3b-3b;

Figure 4 is an enlarged exploded view of the bottle connection device of Figure 2;

Figure 4a is a cross-sectional view of the device of Figure 4 along the line 4a-4a;

Figure 5 is an exploded cross-sectional view of the bottle neck of Figure 2;

Figure 5a is a cross-sectional view of the device of Figure 5 taken along the line 5a-5a;

Fig. 6 is an exploded cross sectional view of the pumping device of sprayer combination of Fig. 2;

Figs. 6a and 6b illustrate the operation of the piston and cylinder and nozzle combination of Fig. 6, Fig. 6a illustrating the piston drawing liquid into the cylinder chamber and Fig. 6b illustrating the piston expelling liquid out of the cylinder chamber;

Fig. 6c is a side elevation view of the cylinder of Fig. 6 taken along the line 6c-6c;

Fig. 7 is a side elevation view in partial cross section of the tip seal of Fig. 6;

Fig. 8 is a front elevation view of Fig. 7 taken along the line 8-8;

Fig. 9a is a cross sectional view of the device of Fig. 6 taken along the line 9a-9a;

Fig. 9b is a cross sectional view of the device of Fig. 6 taken along the line 9b-9b;

Fig. 10 is a top plan view of the cylinder of Fig. 6;

Figs. 11a; 11b and 11c diagrammatically illustrate the operation of the exit nozzle of Fig. 6, Fig. 11a illustrating the nozzle in a wide spray mode, Fig. 11b illustrating the nozzle in a fine stream spray mode, and Fig. 11c illustrating the nozzle in a shut-off mode;

Fig. 11d is a cross sectional view of the nozzle cap of Fig. 6 taken along the line 11d-11d;

Fig. 11e is a cross sectional view of the nozzle tip of Fig. 11d taken along the line 11e-11e;

Figs. 12a and 12b illustrate the operation of the metering device of the sprayer, Fig. 12a illustrating the metering device closing off the flow of fluid there-through, Fig. 12b illustrating the metering device at maximum flow therethrough;

Fig. 13a is a top plan view of the metering dial of Figs. 12a and 12b;

Fig. 13b is a rear plan view of the metering dial of Fig. 13a;

Fig. 13c is a cross sectional view of the control dial of Fig. 13a taken along the line 13c-13c;

Fig. 14 is an enlarged view of the movable portion of the metering device of Figs. 12a and 12b;

Fig. 14a is a bottom plan view of the metering device portion of Fig. 14 taken along the line 15-15;

Fig. 15a is a plan view of the connector piece connecting the metering control wheel to the metering device of Fig. 12a;

Fig. 15b is a side elevation view of the connector piece of Fig. 15a;

Fig. 16 is a cross sectional view of the cut-off gate of Fig. 12b taken along the line 16-16;

Fig. 17 is an alternate embodiment trigger sprayer device;

Fig. 18 is a diagrammatic view of the control device of Fig. 17;

Fig. 19 is a side elevation view in partial cross section of an alternate trigger sprayer device having three fluid containers from which fluids can be drawn;

Fig. 20 is a front elevation view of the trigger spray device of Fig. 19 taken along the line 20-20; and

Fig. 21 is a top plan view of Fig. 20 taken along the line 21-21.

Detailed Description of Preferred Embodiments

The preferred embodiments of the present invention will now be described with reference to the drawings. To facilitate description, any identifying numeral representing an element in one figure will represent the same element in any other figure.

Figs. 1-16 illustrate a preferred embodiment for a trigger sprayer 5 according to the present invention. Figs. 1 and 2 illustrate the trigger sprayer 5 having a sprayer head 10 with a first bottle 220 and a second bottle 240 detachably connected thereto. The first and second bottles 220 and 240 are releasable by operation of respective control tabs 72 and 76. The trigger sprayer 5 includes a trigger 20 which may be manually squeezed by the user to expel fluids out the nozzle cap 60. The user may operably rotate the dial wheel 40 to control relative mixture of fluids from the first and second bottles 220 and 240 by control mechanisms described below. The dial wheel 40 may be continuously variable, have incremental positions such as the six numbered positions (representing selected concentrations 0 - 6) which may have "click stop" ratcheting mechanism, or some other operable feature.

As shown in Fig. 2, the outer shell of the sprayer head 10 is constructed in two pieces or housing portions which attach to one another by a plurality of posts 12 spaced about the head 10. The sprayer head 10 has a trigger mechanism 20 which includes a cylindrical mounting collar 24 to permit pivoting or rotation about a pivot rod 15 which is comparable to one of the pivot posts 12 spaced about the sprayer head 10. The trigger 20 is comprised of an extending handle portion 22 which accepts the fingers of the operator allowing him to squeeze the device to pivot the trigger 20 about the pivot rod 15 thereby engaging the fluid pumping mechanism.

The fluid pumping mechanism is preferably a piston and cylinder combination comprised of a cylinder housing 160 having a piston 140 slidably actuatable therein. The trigger 20 has a lever arm portion 26 extending with a hooked end portion 28 which engages a trigger post 149 on either side of the piston 140.

A biasing means illustrated as a coiled spring 30 is positioned externally to the piston and cylinder combination. The spring 30 is located between extending portion 27 of the trigger 20 and a seat 32 attached to sprayer head housing 10. The spring 30 biases the trigger 20 toward an outward position (i.e. in a clockwise position as viewed in Fig. 2) thereby outwardly urging the trigger arm 22 and consequently urging the piston 140 in a direction to expand the volume within the cylinder 160 for drawing fluid into it.

When the piston 140 moves to draw a vacuum within the cylinder 160, fluid is drawn up from both the first bottle 220 and the second bottle 240. Fluid from the first bottle 220 passes through a first suction tube 235, through a metering means 100, through first tubing 96 and to the cylinder 160. Similarly, fluid from the second bottle 240 is drawn through a second suction tube 255, through connectors 54 & 56, into a second tubing 98, past a shut-off gate 120, and to the cylinder 160. Fluid within the cylinder 160 is then, upon squeezing of the trigger 20 and operation of the piston 140, forced out through the nozzle cap 60.

The first and second tubings 96 and 98 are preferably made from a flexible material so that as the piston 140 reciprocates, the tubings 96 and 98 flex back and forth with the piston movement.

The metering means 100 is controlled by rotation of a dial wheel 40, which is rotationally mounted on a pivot post 45. The metering means 100 is a fluid proportioning device which operates by an axial translation which produces variation in flow restriction of fluid therethrough. Rotation of the dial wheel 40 through connector piece 49 causes the axial translation of the top portion of the metering means 100. The metering means 100 is described in detail below.

As viewed in Figs. 2, 3, 3a, and 3b, the first and second bottles 220 and 240 have identical shell configurations, the shells being generally round or cylindrical on three sides thereof and having flat portions 220a and 240a on the fourth sides thereof. The flat sides 220a and 240a each have a longitudinal groove 230 and 250 and

a longitudinal protrusion 228 and 248 extending from the top shoulder to the bottom thereof. As can be viewed in Figs. 3, 3a, and 3b, the first bottle 220 and the second bottle 240 are placed with their respective flat portions in an engaging relationship, the protrusion or tongue 228 of the first bottle 220 mates with and nests within the groove 250 of the second bottle 240 and the tongue 248 of the second bottle 240 mates with and nests within the groove 230 of the first bottle 220. This nesting arrangement results in a substantially mating relationship which provides a firmness and stability for the first and second bottles 220 and 240 relative to one another. Additionally, because the first and second bottles 220 and 240 are identical, the bottles are interchangeable and only one bottle design need be tooled and manufactured providing economic advantage.

As viewed in Figs. 2-5, each bottle 220 and 240 has a bottle collar 226, 246 which may be inserted into a respective rectangular opening 74, 77 within a respective bottle retainer collar 73, 78. The retainer collars 73, 78 are rotatable through a 90° arc by operation of tabs 72, 76. To illustrate the connection operation and referring to Figs. 2 and 3, once the neck 222 of the first bottle 220 is inserted through the rectangular opening 74 of the retainer collar 73, the tab 72 is then rotated to position the rectangular opening 74 perpendicular to the bottle collar 226, thereby securing the bottle 220 to the sprayer head 10. As viewed in Fig. 3, the bottle collars 226, 246 are also somewhat rectangular (when observed in the plan view of Fig. 3) such that when the bottle collars are aligned, as for example in Fig. 2, the bottle collar 246 of the second bottle 240 may be slid through the bottle retainer collar 78 which has been rotated 90° such that the rectangular opening 77 aligns with the bottle collar 246, and the bottle collar 246 may be inserted through the rectangular opening 77. Once in place, the tab 76 may be actuated, rotating the bottle retainer collar 78 by 90°, as in Fig. 3, which secures the second bottle 240 in place.

In order to operationally describe the connecting apparatus, an example of a preferred application will now be described. The first bottle 220 may be filled with a fluid, such as a concentrated household cleaning fluid, and the second bottle 240 is then filled with a diluting fluid, typically water. The sprayer device then meters out a mixture of the cleaning fluid diluted with water, the household user refilling the second bottle 240 with water as needed.

The fluid connection for the second bottle 240 is illustrated in Figs. 2-4 and 4a. The second suction tube 255 is inserted into a lower nipple 54 in the bottom of a tube retainer piece 50, the tube retainer piece 50 fitting in the bottom of the sprayer head 10. Fluid may pass through the second suction tube 255 through the lower nipple 54, through a passage 53 within the tube retainer piece 50, and then out through an upper nipple 56 into which the second tubing 98 is inserted. The tube retainer piece 50 has a collar section 52 concentric with the lower nipple 54 forming an annular passage 52a therebetween.

The bottle neck 242 may be inserted over and around the concentric collar 52, the collar 52 may have a slight inward taper to allow for a tight sealing fit against the inside surface of the bottle neck 242.

Operationally in a preferred embodiment, the second bottle 240, after being filled with water, may be inserted around the second suction tube 255 into the bottle retainer collar 78, with the bottle neck 242 being firmly pressed around the concentric collar 52. Since the connection between the bottle neck 242 and the concentric collar 52 is airtight or at least substantially leak-proof, air is generally unable to enter the second bottle 240 to replace the volume of fluid which is pumped out through the second suction tube 255. To prevent creation of such vacuum, a venting means is provided to allow for air passage into the second bottle 240.

The preferred venting means includes an air passage through a vent hole 58 in the tube retainer piece 50. To prevent liquid from undesirably leaking out through the vent hole 58, the venting means comprises a retainer seal 90 positioned within the annulus 52a between the concentric collar 52 and the lower nipple 54. The retainer seal 90 is of generally a tubular shape with a first cylindrical portion which fits tightly against the outer surface of the lower nipple 54 and a diagonally outwardly extending or fanning portion 94 extending outward from the cylindrical portion 92 toward the inner surface of the concentric collar 52. The outwardly extending portion 94 fills and seals off the annular space 52a, pressing against the inner surface of the concentric collar 52. Due to its angular orientation, the retainer seal 90 acts as a one-way valve permitting air passing through vent hole 58 to inwardly flex the outwardly extending portion 94 of the retainer seal 90 and to enter the bottle 240 while preventing fluid from the bottle 240 to pass by the retainer seal 90 and leak out of the vent hole 58.

The first bottle 220 has a similar venting means configuration comprised of a plug 260 having an inner nipple 264 and an outer concentric portion 262, the plug being inserted into the neck 222 of the first bottle 220 in a liquid-tight arrangement. The first suction tube 235 is inserted into the inner nipple 264. The upper portion of 264b of the plug nipple 264 is inserted around the nipple 80 of the tube retainer piece 50. The nipple 80 is tapered to allow for a tight sealing fit against the inside surface of the plug nipple 264. An annular passage is provided between the plug nipple 264 and the concentric portion 262 which provides a venting passage for allowing air to enter the bottle 220 to replace fluid being pumped out through the first suction tube 235. A venting means comprised of a retainer seal 90a is provided filling the annular passage 262a so that air passing through vent hole 268 may pass the retainer seal 90a and enter the bottle 220, but fluid is prevented from passing the retainer seal 90a in reaching the vent hole 268. The plug 260 has an upper lip or shoulder 270 so that when it is inserted into the bottle neck 222, it is prevented from being pushed down past the upper rim of the bottle neck 222.

The bottle neck 222 includes male threads 224 even though the threads are not used in the operation of the spray bottle. And as previously described, the first bottle 220 may be filled with a concentrated liquid which will be diluted by the device. A bottle of concentrate may be packaged individually with a screw cap secured over the bottle neck 222. The user need only remove the cap (not shown) and install the bottle 220 as previously described, since the plug 260, the retainer seal 90a and the first suction tube 235 may already be assembled within the first bottle 220. In addition, it may be desirable to switch to another bottle of concentrate, and the removed bottle may be conveniently recapped for storage.

There are several types of pumping means which have been employed in fluid dispensing devices. The preferred piston and cylinder combination and nozzle disclosed herein is illustrated in Figs. 6-11. Fig. 6 illustrates a partially exploded view of the pumping elements comprised primarily of a cylinder housing 160, a piston 140, a nozzle cap 60, and a tip seal 180. The cylinder housing 160 has a rear portion 160a having a rectangular window 162 on either side of. The rectangular window 162 allows for access of the trigger arm 26 to reach the trigger post 149 on the piston 140.

In the front portion of the cylinder housing 160a is the fluid compression chamber 165 where fluid from the first and second bottles 220 and 240 is mixed for ejection to the nozzle 60. A port 163 is located in the downstream end of the cylinder chamber 165 providing fluid communication from the cylinder chamber 165 to the nozzle passage 166. The port 163 has a protrusion or nipple portion 164 extending into the nozzle passage 166.

On the downstream end of the nozzle passage 166 is a shoulder or lip 168 which is positioned to provide a spacing between the front face 60b of the nozzle cap 60 and the front face portion 68a at the end of nozzle passage 166. The nozzle cap 60 has a snap connection 64 which, when the two halves of the sprayer head 10 are assembled, snaps over both halves as viewed in Fig. 2. The nozzle cap 60 has a sealing surface 62 which presses against the lip portion 168 in a sealing arrangement. The tip seal 180 is a elongated flexible rubber piece positioned within a nozzle passage 166 described in more detail below.

The piston 140 has a first passage 142a in fluid communication with the first tubing 96 and a second passage 143a in fluid communication with the second tubing 98. When positioned in the cylinder portion 160, the piston 140 has a front sealing rim 144 sealingly engaging the inner surface of the fluid chamber 165 and a rear rim 146 engaging the inner surface of the rear portion 160a of the cylindrical portion 160. The rear portion 160a of the cylindrical portion 160 may be provided with grooves to correspond to protrusions in the lip portion 146 to ensure that the piston remains in rotational alignment within the cylinder 160.

The piston 140 has a disk-shaped diaphragm 150 installed on its downstream end providing a one-way

valve relationship from the passage exits 142b and 143b. The diaphragm 150 operates as a flapper or butterfly type one-way valve. It has a protrusion portion 152 which snap fits into a groove 145 in the piston 140. As shown in Fig. 6, in its resting state, the diaphragm 150 has a camber of approximately 15° so that when installed upon the piston, the outward wing portions are biased against the exit portions 142b and 143b of the piston 140 establishing a positive sealing pressure against the valve seats 142b and 143b. When the unit is at rest, this positive sealing pressure inhibits fluid leaking from the chamber 165 back into the bottles 220 and 240. This positive sealing pressure also inhibits siphoning of fluids between the bottles 220 and 240 through the chamber 165.

The operations of the retainer seals 90 and 90a also serve to inhibit siphoning of fluids between the bottles 220 and 240. For example, the retainer seal 90 is placed in the annular space 52a in a flexing condition, exerting positive pressure against the side walls to seal off the passage. In order for a siphoning effect (out of bottle 240) to occur, the siphoning force would have to overcome the sealing force of the flexed retainer, so the siphoning effect is inhibited. Similarly, for fluid to be siphoned into the second bottle 240 air would have to be released to make room for any incoming fluid. The retainer seal 90 prevents fluid or air from escaping past the retainer seal 90 thereby inhibiting fluid from even entering the bottle 240.

In operation, when the piston 140 is actuated to the right as viewed in Fig. 6a (by operation of the spring 30 as viewed in Fig. 2), fluid is drawn through the passages 142a and 143a, the diaphragm 150 flexing (as shown in the Fig. 6a) to permit fluid to enter the fluid chamber 165. When the trigger 20 is squeezed, the piston 140 is moved to the left as viewed in Fig. 6b and the fluid within the chamber 165 is compressed, the diaphragm 150 pressing against and sealing off the cylinder ports 142b and 143b forcing fluid out through the port 163 into the nozzle passage 166.

Since the biasing means is external to the cylinder chamber 165, the piston 140 may be pressed all the way to the wall of the cylinder 160 which substantially allows the fluid chamber 165 to be completely emptied.

The divided passage piston 140 permits the fluids from the first and second bottles 220 and 240 remain separated and at their original concentrations all the way to mixing chamber 165.

The tip seal 180 is a highly flexible and preferably elastic elongated member having a plurality of longitudinal ribs 182 spaced around its outer perimeter. At its downstream edge, the tip seal 180 has an outwardly lip or edge 84 forming a front facing recess 184. The lip 84 has a pair of parallel angular gaps 186 which creates a swirling motion when fluid enters into the recess 184.

The tip seal 180 is preferably of one-piece construction. In operation, fluid is allowed to pass in an annular space between the outer circumference of the tip seal 180 along the ribs 182 and the inner wall of the nozzle

passage 166. The tip seal 180 may be sized to substantially fill the nozzle passage 166 so that at the end of the compression stroke of the piston 140, nearly all the fluid mixture may be dispensed out of the nozzle opening 62.

The tip seal 180 also includes a recess or cavity 188 which corresponds to the protrusion 164 of the port 163. The tip seal 180 is axially translatable within the nozzle passage 166 between positions illustrated in Figs. 6a and 6b. During the rearward stroke of the piston 140 filling the fluid chamber 165, the tip seal 180 is drawn rearward as viewed in Fig. 6a with the recess 188 engaging the protrusion 164 effectively sealing off the port 163. During the compression stroke as in Fig. 6b, fluid exiting the ports 163 presses the tip seal 180 downstream to permit exit of fluid through the port 163 and into the nozzle chamber 166. The tip seal 180 functions as the second one-way valve of the positive displacement from piston and cylinder combination.

In a preferred embodiment the tip seal 180 is constructed from a relatively soft and resilient material which is stretched over the protrusion 164 (the protrusion 164 extending further into the cavity 188 than shown in the figures). In operation, the force of fluid exiting the port 163 causes the tip seal cavity 188 to expand and allow the fluid to enter the passage 166. When the fluid flow stops, the tip seal 180 resiliently returns against the protrusion 164 exerting a positive sealing force thereagainst. The flexure of the tip seal 180 itself would inhibit leakage of fluid out the nozzle even when the sprayer is in a resting state.

This functional combination of (1) the cylinder 140 completely emptying the fluid chamber 165, (2) minimizing the volume of left-over fluid downstream of the fluid chamber, and (3) keeping the fluids from the first and second bottles 220 and 240 remain separated and at their original concentrations all the way to mixing chamber 165 all contribute to insuring that a minimum amount of mixed fluid (that is, fluid from a particular actuation) remains in the system for a subsequent actuation. Therefore, when a different fluid mixture setting is selected, a minimum amount of fluid mixture from the previous setting, i.e. substantially only one volume of the fluid chamber 165, is ejected which has the previous setting for concentration mixture.

The nozzle cap 60 includes an exit opening 62 which is tapered having a decreasing diameter. The nozzle opening 62 is eccentrically positioned on the front face of the nozzle cap 60, the nozzle cap 60 being rotatable between positions to select a spray pattern. The nozzle may be positioned to select a wide spray, a fine stream, or a shut-off position.

As viewed in Fig. 6c, the face 168 of the cylinder portion 160 has a pair of stops 169a and 169b which function to assist in the positioning of the rotation nozzle cap 60. In Fig. 11a the nozzle cap 60 is rotated in a counter-clockwise direction with the rotation halted when the stop surface 68c engages the stop 169b thereby positioning the nozzle aperture 62 in line with the tip seal 180. Fluid

swirling through the apertures 186, 186 exits the nozzle aperture 62 in a wide spray pattern.

In Fig. 11b, the nozzle cap 60 is rotated to a position with the stop surface 68c/68b between the stops 169a and 169b. In this position, the nozzle aperture 62 is offset from the tip seal 180 and fluid exiting the nozzle passage 166 is not swirled and therefore exits the nozzle aperture 62 in a fine stream spray pattern.

In Fig. 11c, the nozzle cap 60 has been rotated in a clockwise direction with the rotation halted when the stopping surface 68b engages against the stop 169a. In this position, the location of the nozzle aperture 62 is irrelevant. Referring also to Figs. 11d and 11e, the curved stop surface 68 has a ramp 68a which engages the tip seal 180 when the nozzle cap 60 is rotated into position as illustrated in Fig. 11c. When placed in such position, as viewed in Fig. 6a, the curved stop surface 68 presses against the tip seal 180 forcing it against the port protrusion 164 with the tip seal recess 188 sealing off the port 163 effectively shutting off the exit of fluid therethrough.

The flow control device will now be described with respect to Figs. 12-16. The heart of the flow control device which allows for varying the ratio of fluid mixture between the first bottle to 20 and the second bottle to 40 is the metering means 100. The metering means has an outer cylindrical housing piece 102 and an inner metering rod 110. Fluid from the first bottle 220 passing through the nipple 80 enters into a chamber 112 within the metering rod 110. The base 116 of the metering rod 110 seats within a cylindrical protrusion 82 in the tube retainer piece 50, the base 116 having a lower cylindrical leg portion 114 seating concentrically within the cylindrical portion 82 to provide firm support and additional sealing surface therebetween. Once fluid has passed into the inner chamber 112 of the metering rod 110, it may pass outward through ports 113 and into an annular space between the top portion 110b of the metering rod 110 and the lower portion 102a of the meter housing 102.

By rotation of the dial wheel 40, the meter housing 102 may be axially translated from an off position or low flow position as viewed in Fig. 12a to a high flow position as viewed in Fig. 12b.

Fluid flows between the upper portion 110b of the metering rod 110 and the upper passage 109 of the meter housing 201 through an axial slot 105 cut along the inner surface of the upper portion 102b of the meter housing 102. Except within this passage 105, the upper portion 110b of the metering rod 110 snugly fits within the upper passage 109 of the meter housing 102 thereby finally regulating the flow of fluid through the passage 105.

The depth and width of the passage 105 are gradually reduced from the upstream portion 105a to the downstream portion 105b. If desired, the metering rod 110 may have a position as in Figure 12a which completely shuts off flow of fluid through the passage 105.

In order to prevent leakage of fluid, a sealing mechanism is provided between the metering rod 100 and the

meter housing 102 comprised of a radial rim along an outer circumference adjacent the ports 113, the rim being approximately 0.0127 cm (0.005") high by 0.0508 cm (0.020") wide. In addition metering rod 110 and the meter housing 102 may be constructed from different density materials. In the preferred application, the metering rod 110 is constructed from high density polyethylene and the meter housing is constructed from low density polyethylene. This design and material selection enhance the sliding seal between the metering rod 110 and the meter housing 102.

As viewed in Figures 12a, 12b, 14a, 15a and 15b, the meter housing 102 includes an extending arm 104 having a protrusion which mates into a hole 49b in the connector piece 49. A protrusion 49a on the other end of the connector piece 49 is inserted into a matching hole 45 in the dial wheel 40. The connector 99 is connected to the dial wheel 49 in an off-centred relationship to the centre of the dial wheel 40 such that when the dial wheel 40 is rotated, the meter housing is axially translated as previously described.

Details of the dial wheel 40 are illustrated in Figures 13a, 13b and 13c. Dial wheel 40 has a notch connection 44 secured into a post within the spray head 10 as previously described. A curved ramp 46 with an end ramping portion 46a is positioned along an inner face thereof. As viewed in Figure 12b, when the meter housing is translated into the maximum flow condition, the ramp 46a engages the flow cut-off device 120 as viewed in Fig. 16. The flow cut-off device is a gate device which straddles the second tubing 98 when the ramp 46 engages the upper portion 126 of the cut-off mechanism 120, the sliding gate squeezes the second tubing 98 against a lower edge portion 128 restricting and then cutting off flow of fluid within the second tubing 98. Therefore, at maximum flow out of the first bottle 220, flow from the second bottle is cut-off so that the fluid dispensed is 100% from the first bottle 220.

There are many variations to the above-described preferred embodiments. It has been described that a flow metering or flow ratio varying device may be manually adjusted to select relative flow ratios anywhere between 100% fluid from the first bottle 220 to 100% from the second bottle 240. Of course, an alternate spray head may have ratio limits of any minimum or maximum amount. Alternately, a spray head may be provided without varying control but merely have a preset ratio position which, for example, would spray out a preset concentration of a diluted fluid.

The connection designs for the first and second bottles 220 and 240 as disclosed above were selected for a particular application, but both of the connection designs may be used at either bottle location. For example, a sprayer may be comprised of both bottles having removable and refillable bottle connections as possessed by the second bottle 240.

The materials of construction will be in part dependent upon the types of fluid being used in the bottles. For example, in the application where the first bottle 220 is

filled with high concentration cleaning fluid and the second bottle is filled with water as a diluting fluid, certain materials may be preferred. The tubings, particularly the ones that come in contact with the concentrated cleaning fluid, may be constructed from ethyl-based urethane. The bottles 220 and 240 and the other components in fluid contact with the cleaning fluid may be made from ethyl based polyethylene. The seals, namely the tip seal 180, the diaphragm seal 150, and the retainer seals 90 and 90a may be constructed from compression moulded silicon.

An alternate spray bottle 300 is illustrated in Figures 17 and 18. This sprayer 300 has a sprayer head 305 which is installed on first and second bottles 320 and 325 detachably connected by tabbing mechanism 322 and 327 similar to those as previously described. The sprayer head 305 has a pumping mechanism 310, a trigger 307 and an exit nozzle 309.

Flow ratio control is accomplished by a rotating switch 340 having an actuator handle 315. The switch 340 may have incremental positions or be continuously variable. The handle 315 rotates about an inner shaft 342 to which a cam 344 is attached. The cam 344 rotates within a slot 348 in a sliding gate 350. The gate 350 has protrusions 350a and 350b on opposite ends thereof which, depending upon the position of the switch 315 (and thereby the position of the cam 344) slides to one side or the other depressing the first tubing 330 or the second tubing 335 selectively restricting flow through one or the other thereby controlling the fluid ratio. In the illustration, the tubings 330 and 335 are shown as connected through a "Y" connector 337 before entering the pump mechanism 310, in the invention, however, a pump mechanism and a fluid communication as defined in claim 1 is used.

The preferred embodiment of the present invention is not limited to a two-bottle configuration, and Figures 19 to 21 illustrate a three-bottle combination. The three-bottle design sprayer 400 has a sprayer head 410 mounted upon three bottles, 420, 425 and 430. The bottles 420, 425, and 430 are generally pie-shaped with tongue and groove connections such as 421 and 426 of similar configuration to the two-bottle design previously described. Desirably, each of the bottles is interchangeable as in previous embodiments. The bottles are detachably secured to the head 410 by rotation of tabs 422, 427 and 432 using mechanisms also previously described.

One use for this tri-bottle configuration would be having a first fluid concentrate in the first bottle 425, and a second fluid concentrate in the third bottle 430. The second bottle 420 would then contain the dilution fluid such as water. Both the first bottle 425 and the third bottle 430, have respective metering devices 440a and 440b and respective tubings 450 and 455 leading up to a valving mechanism 435.

By manipulation of the dial wheel 460 (of course, there could be a dial for each metering device) both the metering devices 440a and 440b are actuated to provide

the desired concentration ratio. The upper control device 435 has a handle switch 437 which may be actuated between any desired position, Fig. 21 arbitrarily illustrating three positions namely a first position having fluid completely from the first bottle 425, a second middle position allowing fluid from both the first bottle 425 and the third bottle 430, and a third position permitting fluids solely from the third bottle.

The metering switch 435 may be comprised of the cam construction as that previously described in the previous embodiment in Fig. 18. Similarly, the pumping device 415 may include three passages therethrough so that the fluid mixing takes place in the cylinder chamber as far downstream as possible. Alternatively, the exit port from the metering device 435 may include a "Y" connection so that the pumping device has a two-passage piston as previously described in the embodiment of Figure 1.

Thus, a multiple fluid dispensing apparatus has been shown and described. Though certain examples and advantages have been disclosed, further advantages and modifications may become obvious to one skilled in the art from the disclosures herein. The invention is therefore defined in the claims that follow.

The present application describes subject matter described and claimed in copending EP-Application No. 94120357.2 which was divided from this application.

Claims

1. A fluid dispensing apparatus (5) for mixing and dispensing a first fluid from a first chamber (220) and a second fluid from a second chamber (240), comprising a fluid dispensing head (10), including (a) a fluid outlet (163), (b) a pump chamber (165), (c) pumping means (140,160) for (i) drawing fluid from the first and second chambers (220,240) into the pump chamber (165) at a desired fluid ratio via first and second fluid passages (96,98) in communication with the first and second chambers (220,240) and (ii) discharging fluid out of the pump chamber to the fluid outlet, and (d) an actuator (20) for actuating the pumping means, wherein actuation of the pumping means forces fluid from the pump chamber out through the fluid outlet, characterised in that the first fluid passage (96) provides fluid communication for the first fluid from the first chamber (220) to the pump chamber (165) independently from the second fluid passage (98) which provides fluid communication for the second fluid from the second chamber (240) to the pump chamber (165), whereby the first and second fluid passages (96,98) separately provide fluid communication from the first and second chambers (220,240) into the pump chamber (165).
2. A fluid dispensing apparatus according to claim 1, further comprising a metering device (100) associated with the first fluid passage (96) to obtain the desired fluid ratio.
3. A fluid dispensing apparatus according to claim 2, wherein the metering device (100) comprises an axially translatable flow restriction device (102,110).
4. A fluid dispensing apparatus according to any preceding claim, wherein the first and second chambers (220,240) are constructed as first and second bottles arranged in a side-by-side mating relationship to one another.
5. A fluid dispensing apparatus according to claim 4, wherein the first bottle (220) and the second bottle (240) each includes a collar (226,246) for independently permitting detachable connection of the respective bottle to the fluid dispensing head (20).
6. A fluid dispensing apparatus according to any preceding claim, which includes externally operable ratio adjustment means (40) for selectively varying relative amounts of first and second fluids entering the pump chamber (165).
7. A fluid dispensing apparatus according to any preceding claim, wherein the pump chamber (165) is positioned immediately adjacent the fluid outlet (163) for minimising the amount of mixed fluid not expelled after discharge of fluid.
8. A fluid dispensing apparatus according to any preceding claim, wherein the pumping means comprises a piston (140) and cylinder (160) combination, the piston including first and second internal passages (142a,143a) for providing the fluid communication between the respective fluid passage and the pump chamber (165).
9. A fluid dispensing apparatus according to claim 8, further comprising one-way valves (150) operative with each of the first internal passage (142a) and the second internal passage (143a).
10. A fluid dispensing apparatus according to claim 9, wherein the one-way valves comprise flapper valves (150) disposed on a front face (144) of the piston (140).
11. A fluid dispensing apparatus according to any preceding claim, further comprising a spring (30) for biasing the pumping means (140,160) for drawing fluid into the pump chamber (165), wherein the spring (30) is positioned external to the pump chamber (165) and the actuator comprises a trigger (20), the spring (30) being positioned on the trigger (20).
12. A fluid dispensing apparatus according to any preceding claim, further comprising a third chamber (430) containing a third fluid and a third fluid passage (450) for providing fluid communication for the third

fluid between the third chamber (430) and the pump chamber (165).

13. A fluid dispensing apparatus according to any preceding claim, further comprising a shutoff switch (120) for selectively shutting off fluid communication from one of the chambers to the pump chamber (165). 5
14. A fluid dispensing apparatus according to any preceding claim, further comprising a discharge nozzle passage and rotatable external cap (60) having an aperture (62) therethrough, the aperture (62) being positioned off-centre to be selectively positionable in line with the discharge nozzle passage or offset therefrom. 10 15
15. A fluid dispensing apparatus according to any preceding claim further comprising a discharge nozzle having (a) a protruding orifice (164) extending outward from a side of the pump chamber (165) into a nozzle chamber (166), (b) a tip seal (180) positioned in the nozzle chamber and having (i) a plurality of longitudinal ribs (182) forming a fluid passage in the nozzle chamber (166) external to the tip seal and (ii) a closed cavity (188) in a first end thereof for enclosing and sealing off the protruding orifice (164), the tip seal (180) being axially translatable during actuation of the pumping means (140, 160), the tip seal moving to seal off the protruding orifice (164) during fluid intake of the pumping means and moving away from the protruding orifice during discharge of fluid therefrom. 20 25 30
16. A fluid dispensing apparatus according to Claim 15 wherein the tip seal (180) includes a swirl cavity means in its second end for directing fluid from the nozzle chamber (166) in a circular motion. 35
17. A fluid dispensing apparatus according to any preceding claim, wherein the fluid dispensing head is a trigger sprayer comprising a piston (140) and cylinder (160) combination, a trigger (20) for actuating the piston (140), and a cylinder chamber (165) within the cylinder (160). 40 45
18. A fluid dispensing apparatus according to any one of the preceding claims, further comprising a bottle (220) constructed and arranged in a substantially mating relationship to at least a second bottle (240) of similar configuration and said bottle (220) having a collar connector (226) for permitting detachable connection to the handheld fluid dispensing device (10) independent and separate from the second bottle, said bottles forming said first and second chambers. 50 55
19. A fluid dispensing apparatus according to claim 18, wherein the bottle (220) has a generally cylindrical

shape on three sides with a generally flat planar fourth side (220a), the planar fourth side containing a longitudinal groove (230) and a longitudinal tongue (228) extending to a bottom of the bottle.

20. A fluid dispensing apparatus according to claim 19, wherein the planar fourth side (220a) is mateable with a planar fourth side of a second bottle (240) of identical configuration in a side by side relationship below the handheld fluid dispensing system.
21. A fluid dispensing apparatus according to claim 19, wherein the planar fourth side (220a) has a mating surface for mating with and corresponding to an identical planar side of an identical second bottle (240), said mating surface having a number of grooves equal to a number of protrusions thereon.
22. A fluid dispensing apparatus according to claim 18, wherein the bottle (220) further comprises (a) a neck portion (222), (b) a retainer plug (260) positioned within the neck portion (222), the retainer plug having an inner passage (264b) and an outer annular passage (262a), and (c) a seal (90a) positioned in the outer annular passage (262a) for permitting air to enter the bottle (220) through the annular passage and inhibiting fluid from exiting the bottle out through the annular passage.
23. A fluid dispensing apparatus according to claim 18, wherein the collar connector includes a pair of outwardly extending ears (226, 246) spaced about said neck portion (222) for detachable connection to a retainer connector (73) of a handheld fluid dispensing device (10).

Patentansprüche

1. Fluidausgabevorrichtung (5) zum Mischen und Ausgeben eines ersten Fluids aus einer ersten Kammer (220) und eines zweiten Fluids aus einer zweiten Kammer (240), mit einem Fluidausgabekopf (10), der (a) einen Fluidauslaß (163), (b) eine Pumpenkammer (165), (c) Pumpmittel (140, 160) zum (i) Abziehen von Fluid aus den ersten und zweiten Kammern (220, 240) in die Pumpenkammer (165) in einem gewünschten Fluidverhältnis durch erste und zweite Fluiddurchgänge (96, 98), die in Fließverbindung mit den ersten und zweiten Kammern (220, 240) stehen, und (ii) zum Auslassen des Fluids aus der Pumpenkammer zu dem Fluidauslaß, und (d) ein Betätigungsglied (20) zum Betätigen der Pumpmittel umfaßt, wobei die Betätigung der Pumpmittel das Fluid aus der Pumpenkammer heraus durch den Fluidauslaß drückt, dadurch gekennzeichnet, daß der erste Fluiddurchgang (96) für das erste Fluid eine Fluidverbindung von der ersten Kammer (220) zu der Pumpenkammer (165) unabhängig von dem zweiten Fluiddurchgang (98) vor-

sieht, der eine Fluidverbindung für das zweite Fluid von der zweiten Kammer (240) zu der Pumpenkammer (165) vorsieht, wodurch die ersten und zweiten Fluiddurchgänge (96,98) getrennt voneinander eine Fluidverbindung von den ersten und zweiten Kammern (220,240) zu der Pumpenkammer (165) vorsehen.

2. Fluidausgabevorrichtung nach Anspruch 1, desweiteren mit einer Dosiereinrichtung (100), die dem ersten Fluiddurchgang (96) zugeordnet ist, um das gewünschte Fluidverhältnis zu erhalten.
3. Fluidausgabevorrichtung nach Anspruch 2, bei der die Dosiereinrichtung (100) eine axial verschiebbare Strömungsdruckeinstellung (102,110) umfaßt.
4. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, bei der die ersten und zweiten Kammern (220, 240) als erste und zweite Flaschen aufgebaut sind, die in einer zusammenpassenden Beziehung zueinander Seite an Seite angeordnet sind.
5. Fluidausgabevorrichtung nach Anspruch 4, bei der die erste Flasche (220) und die zweite Flasche (240) jeweils einen Ansatz (226,246) umfassen, der unabhängig voneinander eine abnehmbare Verbindung der jeweiligen Flasche mit dem Fluidausgabekopf (20) erlaubt.
6. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, die ein äußerlich betätigbares Verhältnis-Einstellmittel (40) zum selektiven Variieren der Relativbeträge der ersten und zweiten Fluide umfaßt, die in die Pumpenkammer (165) gelangen.
7. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, bei der die Pumpenkammer (165) direkt neben dem Fluidauslaß (163) angeordnet ist, um den Betrag an gemischtem Fluid zu minimieren, der nach der Ausgabe des Fluids nicht ausgestoßen wird.
8. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, bei der das Pumpmittel eine Kombination aus einem Kolben (140) und einem Zylinder (160) umfaßt, wobei der Kolben erste und zweite innere Durchgänge (142a,143a) zum Vorsehen der Fluidverbindung zwischen dem jeweiligen Fluiddurchgang und der Pumpenkammer (165) umfaßt.
9. Fluidausgabevorrichtung nach Anspruch 8, desweiteren mit Einwegventilen (150), die sowohl mit dem ersten inneren Durchgang (142a) als auch mit dem zweiten inneren Durchgang (143a) betriebsbereit sind.

10. Fluidausgabevorrichtung nach Anspruch 9, bei der die Einwegventile Klappenventile (150) umfassen, die sich auf einer Vorderseite (144) des Kolbens (140) befinden.
11. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, desweiteren mit einer Feder (30) zum Vorspannen der Pumpmittel (140,160) zum Abziehen von Fluid in die Pumpenkammer (165), wobei die Feder (30) außerhalb der Pumpenkammer (165) angeordnet ist und das Betätigungsglied einen Drucker (20) umfaßt, wobei die Feder (30) auf dem Drucker (20) angeordnet ist.
12. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, desweiteren mit einer dritten Kammer (430), die ein drittes Fluid und einen dritten Fluiddurchgang (450) zum Vorsehen einer Fluidverbindung für das dritte Fluid zwischen der dritten Kammer (430) und der Pumpenkammer (165) enthält.
13. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, desweiteren mit einem Absperrschalter (120) zum wahlweisen Absperrern der Fluidverbindung von einer der Kammern zu der Pumpenkammer (165).
14. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, desweiteren mit einem Strahldüsendurchgang und einer drehbaren äußeren Abdeckung (60), durch die eine Öffnung (62) ausgebildet ist, wobei die Öffnung (62) außermittig angeordnet ist, so daß sie wahlweise in Reihe mit dem Strahldüsendurchgang oder versetzt dazu positioniert werden kann.
15. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, desweiteren mit einer Strahldüse, die (a) eine vorstehende Mündung (164), die sich nach außen von einer Seite der Pumpenkammer (165) aus in eine Düsenkammer (166) erstreckt, und (b) eine Enddichtung (180) umfaßt, die sich in der Düsenkammer befindet und (i) eine Vielzahl von Längsrippen (182), die einen Fluiddurchgang in der Düsenkammer (166) außerhalb der Enddichtung bilden, und (ii) eine geschlossene Höhlung (188) in einem ersten Ende davon aufweist, um die vorstehende Mündung (164) zu umschließen und abzudichten, wobei die Enddichtung (180) während der Betätigung der Pumpmittel (140,160) axial verschiebbar ist, wobei die Enddichtung bewegt wird, um die vorstehende Mündung (164) während der Fluidaufnahme der Pumpmittel abzudichten und um sich von der vorstehenden Mündung während der Ausgabe des Fluids daraus wegzubewegen.
16. Fluidausgabevorrichtung nach Anspruch 15, bei der die Enddichtung (180) ein Wirbelhohlraummittel in

ihrem zweiten Ende umfaßt, um das Fluid aus der Düsenkammer (166) in eine kreisförmige Bewegung auszurichten.

17. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, bei der der Fluidausgabekopf eine Drückersprayvorrichtung ist, die eine Kombination aus einem Kolben (140) und einem Zylinder (160), einen Drücker (20) zum Betätigen des Kolbens (140) und eine Zylinderkammer (165) in dem Zylinder (160) umfaßt. 5
18. Fluidausgabevorrichtung nach einem der vorhergehenden Ansprüche, desweiteren mit einer Flasche (220), die so aufgebaut und angeordnet ist, daß sie sich in einer im wesentlichen zusammenpassenden Beziehung zu mindestens einer zweiten Flasche (240) mit einer ähnlichen Konfiguration befindet, und wobei diese Flasche (220) ein Ansatzverbindungsstück (226) aufweist, um eine abnehmbare Verbindung mit der handgehaltenen Fluidausgabevorrichtung (10) unabhängig und getrennt von der zweiten Flasche zu erlauben, wobei die Flaschen die ersten und zweiten Kammern bilden. 10
19. Fluidausgabevorrichtung nach Anspruch 18, bei der die Flasche (220) im allgemeinen auf drei Seiten zylinderförmig ist und eine im allgemeinen flache ebene vierte Seite (220a) aufweist, wobei die ebene vierte Seite eine Längsnut (230) und eine Längszunge (228) umfaßt, die sich bis zu einem Boden der Flasche erstrecken. 15
20. Fluidausgabevorrichtung nach Anspruch 19, bei der die ebene vierte Seite (220a) mit einer ebenen vierten Seite einer zweiten Flasche (240) mit gleicher Konfiguration unterhalb des handgehaltenen Fluidausgabesystems in eine zusammenpassende, nebeneinanderliegende Beziehung gebracht werden kann. 20
21. Fluidausgabevorrichtung nach Anspruch 19, bei der die ebene vierte Seite (220a) eine passende Oberfläche aufweist, die mit einer identischen ebenen Seite einer identischen zweiten Flasche (240) zusammenpaßt und dieser entspricht, wobei die zusammenpassende Oberfläche eine Anzahl von Nuten aufweist, die gleich einer Anzahl von darauf ausgebildeten Vorsprüngen ist. 25
22. Fluidausgabevorrichtung nach Anspruch 18, bei der die Flasche (220) außerdem (a) einen Halsabschnitt (222), (b) einen Rückhaltestopfen (260), der in dem Halsabschnitt (222) positioniert ist, wobei der Rückhaltestopfen einen inneren Durchgang (264b) und einen äußeren ringförmigen Durchgang (262a) aufweist, und (c) eine Dichtung (90a) umfaßt, die in dem äußeren ringförmigen Durchgang (262a) angeordnet 30

net ist, um zu erlauben, daß Luft in die Flasche (220) durch den ringförmigen Durchgang eintreten kann, und um zu verhindern, daß Fluid durch den ringförmigen Durchgang aus der Flasche austritt.

23. Fluidausgabevorrichtung nach Anspruch 18, bei der das Ansatzverbindungsstück ein Paar von sich nach außen erstreckenden Ohren (226, 246) umfaßt, die voneinander um den Halsabschnitt (222) beabstandet sind, um eine abnehmbare Verbindung mit einem Aufnahmeverbindungsstück (73) einer handgehaltenen Fluidausgabevorrichtung (10) zu ermöglichen. 35

Revendications

1. Dispositif (5) de distribution de fluide pour mélanger et distribuer un premier fluide provenant d'une première chambre (220) et un second fluide provenant d'une seconde chambre (240), comportant une tête (10) de distribution de fluide, comprenant (a) une sortie (163) de fluide, (b) une chambre (165) de pompe, (c) un moyen de pompage (140, 160) pour (i) entraîner un fluide depuis les première et seconde chambres (220, 240) jusque dans la chambre (165) de pompe dans des proportions de fluides voulues via un premier et un second passages (96, 98) de fluides communiquant avec les première et seconde chambres (220, 240); et (ii) refouler un fluide hors de la chambre de pompe jusqu'à la sortie de fluide, et (d) un actionneur (20) pour actionner le moyen de pompage, l'actionnement du moyen de pompage expulsant le fluide depuis la chambre de pompe via la sortie de fluide, caractérisé en ce que le premier passage (96) de fluide assure, pour le premier fluide, une communication de fluide depuis la première chambre (220) jusqu'à la chambre (165) de pompe d'une manière indépendante du second passage (98) de fluide qui assure pour le second fluide une communication de fluide depuis la seconde chambre (240) jusqu'à la chambre (165) de pompe, les premier et second passages (96, 98) de fluide assurant séparément une communication de fluide depuis les première et seconde chambres (220, 240) jusqu'à la chambre (165) de pompe. 40
2. Dispositif de distribution de fluide selon la revendication 1, comportant en outre un dispositif de dosage (100) associé au premier passage (96) de fluide pour obtenir les proportions de fluides voulues. 45
3. Dispositif de distribution de fluide selon la revendication 2, dans lequel le dispositif de dosage (100) comporte un dispositif (102, 110) limiteur de débit à mouvement axial. 50
4. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, dans 55

lequel les première et seconde chambres (220, 240) sont réalisées sous la forme d'une première et d'une seconde bouteilles accouplées côte à côte l'une avec l'autre.

5. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, dans lequel la première bouteille (220) et la seconde bouteille (240) comportent chacune une bague (226, 246) permettant de manière indépendante un raccordement séparable de la bouteille respective à la tête (20) de distribution de fluide. 5
6. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, comportant un moyen de réglage (40) de proportions, actionnable de l'extérieur, pour modifier à volonté les quantités relatives de premier et second fluides pénétrant dans la chambre (165) de pompe. 10
7. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, dans lequel la chambre (165) de pompe est placée de manière immédiatement contigue à la sortie (163) de fluide pour limiter la quantité de fluide mélangé non expulsée après le refoulement de fluide. 15
8. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, dans lequel le moyen de pompage comprend une combinaison d'un piston (140) et d'un cylindre (160), le piston comportant un premier et un second passages internes (142a, 143a) pour assurer la communication de fluide entre le passage respectif de fluide et la chambre (165) de pompe. 20
9. Dispositif de distribution de fluide selon la revendication 8, comportant en outre des soupapes unidirectionnelles (150) coopérant avec chacun des premier passage interne (142a) et second passage interne (143a). 25
10. Dispositif de distribution de fluide selon la revendication 9, dans lequel les soupapes unidirectionnelles comportent des clapets (150) à battant disposés sur une face antérieure (144) du piston (140). 30
11. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, comportant en outre un ressort (30) servant à solliciter le moyen de pompage (140, 160) pour entraîner un fluide jusque dans la chambre (165) de pompe, le ressort étant placé à l'extérieur de la chambre (165) de pompe et l'actionneur comportant une gâchette (20), le ressort étant placé sur la gâchette (20). 35
12. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, comportant en outre une troisième chambre (430) 40

contenant un troisième fluide et un troisième passage (450) de fluide qui assure pour le troisième fluide une communication de fluide entre la troisième chambre (430) et la chambre (165) de pompe.

13. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, comportant en outre un robinet de sectionnement (120) pour couper à volonté la communication de fluide entre une des chambres et la chambre (165) de pompe. 45
14. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, comportant en outre un passage de buse de refoulement et un bouchon extérieur rotatif (60) que traverse une ouverture (62), l'ouverture (62) étant dans une position décentrée, ce qui permet, à volonté, d'aligner l'ouverture avec le passage de buse de refoulement ou de la décaler par rapport au passage. 50
15. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, comportant en outre une buse de refoulement ayant (a) un orifice saillant (164) s'étendant vers l'extérieur depuis un côté de la chambre (165) de pompe jusque dans une chambre (166) de buse, (b) un joint d'étanchéité (180) d'extrémité placé dans la chambre de buse et ayant (i) une pluralité de nervures longitudinales (182) formant dans la chambre (166) de buse un passage de fluide à l'extérieur du joint d'étanchéité d'extrémité et (ii) une cavité (188) fermée à une première extrémité de celui-ci pour entourer et isoler l'orifice saillant (164), le joint (180) d'étanchéité pouvant être déplacé axialement pendant l'actionnement du moyen de pompage (140, 160), le joint d'étanchéité d'extrémité se déplaçant pour empêcher l'accès à l'orifice saillant (14) pendant l'admission de fluide par le moyen de pompage et s'éloignant de l'orifice saillant pendant le refoulement de fluide depuis celui-ci. 55
16. Dispositif de distribution de fluide selon la revendication 15, le joint d'étanchéité (180) d'extrémité comporte à sa seconde extrémité une cavité de tourbillonnement pour diriger le fluide en un mouvement circulaire depuis la chambre (166) de buse.
17. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, dans lequel la tête de distribution de fluide est un pulvérisateur à gâchette comprenant un ensemble de piston (140) et cylindre (160), une gâchette (20) pour actionner le piston (140), et une chambre (165) de cylindre à l'intérieur du cylindre (160).
18. Dispositif de distribution de fluide selon l'une quelconque des revendications précédentes, comportant en outre une bouteille (220) construite et placée d'une manière sensiblement accouplée avec au

moins une seconde bouteille (240) d'une configuration similaire et ladite bouteille (220) ayant un raccord (226) à bague pour permettre un raccordement séparable au dispositif portatif (10) de distribution de fluide indépendant et séparé de la seconde bouteille, lesdites bouteilles formant lesdites première et seconde chambres.

19. Dispositif de distribution de fluide selon la revendication 18, dans lequel la bouteille (220) a une forme globalement cylindrique sur trois côtés avec un quatrième côté plan (220a) globalement plat, le quatrième côté plan comportant une gorge longitudinale (230) et une languette longitudinale (228) s'étendant jusqu'au fond de la bouteille. 10 15
20. Dispositif de distribution de fluide selon la revendication 19, dans lequel le quatrième côté plan (220a) peut être accouplé, côte à côte, avec un quatrième côté plan d'une seconde bouteille (240) à configuration identique, sous le système portatif manuel de distribution de fluide. 20
21. Dispositif de distribution de fluide selon la revendication 19, dans lequel le quatrième côté plan (220a) a une surface d'accouplement pour accouplement avec et correspondant à un côté plan identique d'une seconde bouteille identique (240), ladite surface d'accouplement ayant un nombre de gorges égal à un nombre de saillies sur celle-ci. 25 30
22. Dispositif de distribution de fluide selon la revendication 18, la bouteille (220) comporte en outre (a) une partie formant col (222), (b) un bouchon de retenue (260) placé dans la partie formant col (222), le bouchon de retenue ayant un passage intérieur (264b) et un passage extérieur annulaire (262a), et (c) un joint d'étanchéité (90a) placé dans le passage extérieur annulaire (262a) pour permettre à de l'air d'entrer dans la bouteille (220) par le passage annulaire et pour empêcher le fluide de sortir de la bouteille par le passage annulaire. 35 40
23. Dispositif de distribution de fluide selon la revendication 18, dans lequel le raccord à bague comporte une paire de pattes (226, 246) s'étendant vers l'extérieur, espacées autour de ladite partie formant col (222) pour permettre un raccordement séparable à un raccord de retenue (73) d'un dispositif portatif (10) de distribution de fluide. 45 50

55




FIG. 1.


























FIG. 3.














FIG. 18.




FIG. 17.

